



NOTES:

1. TO BE USED ONLY IN TYPE 2 CURB AND GUTTER WITH 2" DEPRESSION. USE IN TYPE 1A CURB AND GUTTER ONLY UPON APPROVAL OF THE CITY ENGINEER. SEE KEYNOTE 1.
2. FACE ANGLE SHALL BE CAST INTO STRUCTURE CONTINUOUS FOR THE FULL LENGTH "W".
3. ALL EXPOSED METAL PARTS TO BE HOT-DIPPED GALVANIZED AFTER FABRICATION.
4. WHEN CURB INLET OPENING HEIGHT (H) EXCEEDS 6" INSTALL 1" Ø STEEL PROTECTION BAR.
5. INSTALL ADDITIONAL BARS AT 3-1/2" CLEAR SPACING ABOVE FIRST BAR WHEN OPENING EXCEEDS 13".
6. WHEN CURB INLET OPENING LENGTH EXCEEDS 8' INSTALL 1" Ø STEEL SUPPORT BOLTS, SPACED AT NOT MORE THAN 5' O.C.

KEYNOTES:

1. ALTERNATE ANGLE IRON SIZE, DEPRESSION DEPTH, AND SLAB THICKNESS MAY BE USED UPON APPROVAL OF THE CITY ENGINEER.

DATE: 09/22/2017		NOT TO SCALE	
REVISION	BY	APPROVED	DATE

CITY OF ELK GROVE - PUBLIC WORKS

**CATCH BASIN FACE PLATE
ASSEMBLY AND PROTECTION BAR**

APPROVED BY:
Robert Murdoch
CITY ENGINEER

10/24/2018
DATE

DRAWING NUMBER
SD - 17

